

### **Amendments to the Specification:**

*Please add the following new paragraph after paragraph [0025]:*

Figure 8 is a side view of a component part container delivery rack system.

*Please amend paragraph [0027] as shown below:*

The rack 10 includes a hook 44 and hook receptacle 46. The hook 44 is adapted to be connected to a tow motor truck 45 or the hook receptacle 46 of another delivery rack 10 as shown in Figure 8. The hook 44 is detachable from the hook receptacle 46 to permit arrangement of the delivery racks as a train.

*Please amend paragraph [0028] as shown below:*

First and second locking elements 48 and 50 are provided on the front transverse rail 22 and back transverse rail 26, respectively. The locking elements 48 and 50 are used to retain dollies 76 that will be described with reference to Figures 5-7 below within the first and second compartments 16 and 18. Roller guides 52 are provided on the transverse rails on the front and rear sides of the first and second compartments 16 and 18. The roller guides 52 may include a first roller guide 52' that is downwardly offset relative to the other roller guides 52 so that the dolly 76 may be lifted slightly as it is inserted into ~~the compartments~~ compartment 16[, ] or 18. The dolly 76 is lifted so that when the delivery rack 10 is moved with dolly 76 in ~~the compartments~~ a compartment 16, 18, the wheels of each dolly 76 will be spaced slightly from the floor. The dolly 76 is adapted to support one or more component part containers 78.